VAPPRO OILFIELD PRODUCTS





VAPPRO OP 531 Proprietary blend of fatty Imidazoline Protects Oil & Gas Pipelines Against CO₂ And H₂S

INTRODUCTION

Despite the fact that carbon steel has low resistance to CO_2 environments, it is widely used in the petroleum industry mainly due to economical reasons. Carbon dioxide (CO_2) corrosion of carbon steel pipelines and equipment in the oil and gas industry has been given much attention in recent years because of an increased tendency to inject CO_2 into oil wells to reduce the viscosity of oil and increase the its production. Internal corrosion of carbon steel pipelines is a major problem encountered in the oil and gas industry.

Vappro OP 531 is a proprietary corrosion inhibitor developed specially to combat carbon dioxide and hydrogen sulphide in oil and gas pipelines.

Magna

HEADQUARTERS, SINGAPORE

Magna International Pte Ltd 10H, Enterprise Road, Singapore 629834. Tel (65) 6788-1228 Fax (65) 6785-1497 Email info@magnachem.com.sg Website http://www.magnachem.com.sg

NORTH AMERICA

1450 Government Road West Kirkland Lake, Ontario P2N 2E9 Canada Tel 1.416 479 9151 Fax 1.888 317 1993 Email magna@vappro.com Website: http://www.vappro.com

DESCRIPTION

Vappro OP 531 is a free flowing slight amber liquid specially developed to combat Hydrogen Sulfide, and Carbon dioxide commonly found in crude oil processing equipment, pipelines, refinery and petrochemical plant equipment and system.

Vappro OP 531 is an excellent product for protecting the above said equipment against corrosion caused by carbon dioxide and hydrogen sulphide by forming a corrosion inhibiting barrier film. In addition, Vappro OP 531 provides a continuous vapour inhibitor to protect areas that are inaccessible through direct solution contact.

FEATURES

- Exhibits excellent corrosion inhibition properties against Hydrogen Sulfide, and Carbon dioxide and Oxygen
- Prevents stress corrosion cracking (SCC) and hydrogen embrittlement.VCI phase provides continuous protection to inaccessible areas of the equipment.
- Eliminates pitting corrosion
- Inhibitor forms a an excellent barrier on surface of the equipment against corrosive gases.
- Post lingering corrosion inhibition effect.
- Nitrite-Free
- Contains no heavy metal
- Protects both ferrous and non-ferrous metals
- Available in concentrate form to reduce inventory shipment cost.



VAPPRO OP 531





Severe corrosions found on pipes

| TYPE OF CORROSIVE MEDIUM | METHOD OF APPLICATION | DOSAGE |
|--------------------------|------------------------------|----------------|
| H ₂ S | Fogging/Continuous Injection | 8000-10,000ppm |
| CO ₂ | Fogging/Continuous Injection | 350-500ppm |
| 0 ₂ | Fogging/Continuous Injection | 250-300ppm |
| Moisture | Fogging | 1000-1500ppm |

TYPICAL PROPERTIES

Appearance

Clear Liquid

Color

Amber

Viscosity

Free Flowing Liquid

pН

9 - 10.5 (1% solution)

AREAS OF USE

- Oil wells and equipment
- Pipelines and collection systems for waterencroached crude oil
- Refinery processing equipment
- Petrochemical plant equipment and systems
- Crude Oil processing equipment
- Crude Oil pipes

Packaging: 20 liter HPDE Pail or 209 liter Steel Drum

For more information about VAPPRO products, please request for VAPPRO PRODUCT GUIDE from any VAPPRO representative.

Please contact our distributor or reseller for more information:

| Tayna | |
|---------------|-----------|
| HEADQUARTERS, | SINGAPORE |

Mogno

Magna International Pte Ltd 10H, Enterprise Road, Singapore 629834. Tel (65) 6788-1228 Fax (65) 6785-1497 Email info@magnachem.com.sg Website http://www.magnachem.com.sg

NORTH AMERICA

1450 Government Road West Kirkland Lake, Ontario P2N 2E9 Canada Tel 1.416 479 9151 Fax 1.888 317 1993 Email magna@vappro.com Website: http://www.vappro.com

Copyright 2007. The details of our products are given completely free of undertaking. Since their application lies outside our control, we cannot accept any liability for the results. User shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.